UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/573,754	03/29/2006	Tatsuya Nakazawa	029471-0201	4000

22428   7590   10/01/2009
FOLEY AND LARDNER LLP
SUITE 500
3000 K STREET NW
WASHINGTON, DC 20007

EXAMINER
MASUR, PAUL H

ART UNIT	PAPER NUMBER
2416	

MAIL DATE	DELIVERY MODE
10/01/2009	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
Office Action Summary	10/573,754	NAKAZAWA ET AL.
	Examiner	Art Unit
	Paul Masur	2416

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE <u>3</u> MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
  Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1) ☒ Responsive to communication(s) filed on <u>10 June 2009</u>.
2a) ☒ This action is **FINAL**.   2b) ☐ This action is non-final.
3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4) ☒ Claim(s) <u>1-71</u> is/are pending in the application.
   4a) Of the above claim(s) <u>1-47 and 63</u> is/are withdrawn from consideration.
5) ☒ Claim(s) <u>64-67 and 69</u> is/are allowed.
6) ☒ Claim(s) <u>48-62,68,70 and 71</u> is/are rejected.
7) ☐ Claim(s) _____ is/are objected to.
8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9) ☐ The specification is objected to by the Examiner.
10) ☒ The drawing(s) filed on <u>29 March 2006</u> is/are: a)☒ accepted or b)☐ objected to by the Examiner.
    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
    a)☒ All   b)☐ Some * c)☐ None of:
    1. ☐ Certified copies of the priority documents have been received.
    2. ☐ Certified copies of the priority documents have been received in Application No. _____.
    3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☐ Notice of References Cited (PTO-892)
2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
3) ☒ Information Disclosure Statement(s) (PTO/SB/08)
   Paper No(s)/Mail Date <u>08/06/2009</u>.
4) ☐ Interview Summary (PTO-413)
   Paper No(s)/Mail Date. _____ .
5) ☐ Notice of Informal Patent Application
6) ☐ Other: _____ .

DETAILED ACTION

Information Disclosure Statement

1.   **The information disclosure statement (IDS) submitted on 08/06/2009 was filed after the mailing date of the first action on 03/11/2009.** The submission is in compliance with the provisions of 37 CFR 1.97. Accordingly, the information disclosure statement is being considered by the examiner.

Response to Arguments

2.   **Applicant's arguments, see page 18, filed 06/10/2009, with respect to claim objections have been fully considered and are persuasive.** The objection of claims 52-52 has been withdrawn.

3.   **Applicant's arguments, see page 24, filed 06/10/2009, with respect to the specification have been fully considered and are persuasive.** The objection of the specification has been withdrawn.

4.   **Applicant's arguments filed 06/10/2009 have been fully considered but they are not persuasive.**

    On pages 19 and 20 of the remarks, in regard to claims 48, 56, 68, and 70, the applicant submits that Cooklev fails to teach *"decision means for deciding on whether data from at least one of said first and second communication networks has been delayed or lost."* The applicant further submits that Cooklev, column 9, lines 29-43 fails to teach that the packet processor does not disclose whether packets have been delayed or lost.

The examiner respectfully disagrees with these arguments. The examiner kindly directs the applicant to the cited passage of Cooklev and to Figure 5, which was also cited with Cooklev in the examiner's previous action (see page 3). The reference states, "The packet processor 704 extracts the sequence number present in the header of every packet and detects, first, whether packets have arrived in order, and, second, the presence of packet loss." Therefore, the packet processor does examine packets for loss or delay.

Cooklev discloses that packets are read by their sequence number. For example, the packet processor in Cooklev, for simplicity sake, reads packets with sequence numbers in the following order: 1-3-2-4. According to the functionality disclosed in Cooklev, the packet processor would determine that packets were not received in order. Furthermore, Cooklev also states that the packet processor would also detect packet loss if packets with the following sequence numbers were detected: 1-3-4-5-7-...and so on. Lastly, the examiner kindly directs the applicant to Figure 5, where the labeled arrows from element 704 (the packet processor) clearly indicate the operation of the device for the following scenarios: Lost Unimportant Packet, No Missing Packet, and Lost Important Packet. Therefore, it seems clear to the examiner that Cooklev discloses the limitation in its entirety.

On pages 20 and 21 of the remarks, in regard to claims 48, 56, 68, and 70, the applicant submits that Cooklev fails to teach *"if the result of said decision indicated that the data from at least one of said first and second communication networks has been delayed in arrival or lost, data for causing a destination terminal of transmission on*

the other communications network to execute error concealment processing is

generated or data acquired is discarded." The applicant further submits that Cooklev,

column 9, lines 47-51, and Figure 5, element 710 fail to disclose the limitation. The

applicant further submits that Cooklev, column 9, lines 47-51, Figure 6 discloses that an

important lost packet, the packet reconstruction block tries to recover a lower quality

version of the lost data from other packets. The applicant also submits Cooklev, column

9, lines 51-59 states that a lower quality version of the missing data packet is

reconstructed into a lower-quality version of the lost packet, and dithering signals are

made available to a dither subtraction process.

The examiner respectfully disagrees with these arguments. The examiner kindly

directs the applicant to the explanation listed above. In addition, the examiner also

kindly directs the applicant to the citations listed in the previous action (see pages 3 and

4). Cooklev, as stated previously, does teach that the packet processor indicates if a

packet is lost or an error occurred in transmission. In addition, Cooklev teaches several

methods for handling lost packets, of which the examiner cited one. Element 710 of

Figure 6 teaches reconstructing a lost packet (which happened to be deemed important

by the packet processor). Lastly, the use of a dithering process to provide error

concealment through packet reconstruction further clarifies the teachings of the claim

limitation. Therefore, it seems clear to the examiner that Cooklev discloses this

limitation in entirety.

On page 21 of the remarks, in regard to claims 48, 56, 68, and 70, the

applicant submits that Cooklev fails to teach all of the limitations of the claims. The

applicant further submits that M.P.E.P. § 2131 states that"[t]he identical invention must be shown in as complete detail as is contained in the claim." *Richardson v. Suzuki Motor Co.*, 868 F.2d 1226, 1236 (Fed. Cir. 1989).

The examiner respectfully disagrees for the reasons listed above in light of the claim language and the references cited. In addition, the examiner directs the applicant to M.P.E.P. § 2111 which states "During patent examination, the pending claims must be "given their broadest reasonable interpretation consistent with the specification." >The Federal Circuit's en banc decision in *Phillips v. AWH Corp.*, 415 F.3d 1303, 75 USPQ2d 1321 (Fed. Cir. 2005)." Therefore, the examiner reserves the right to give the claims their broadest reasonable interpretation in light of the specification.

On pages 21 and 22 of the remarks, in regard to claims 49-55, 57, 59-62, and 71, the applicant submits that for previously discussed reasons Cooklev fails to teach the limitations of the related parent claims, which in turn recite similar limitations previously disclosed in claims 48, 56, 68, and 70. In addition, the applicant submits that the reference Joseph et al. fails to cure these limitations.

The examiner respectfully disagrees with these arguments. The examiner kindly directs the applicant to the arguments listed above.

Claim Rejections - 35 USC § 102

5.   **The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:**

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

6. **Claims 48, 56, 58, & 68 are rejected under 35 U.S.C. 102(e) as being anticipated by Cooklev (US Patent No. 6,574,218).**

7. **As per claim 48,** Cooklev teaches a gateway apparatus for conducting connection between a first communication network and a second communication network of respective different types [Cooklev, fig. 2, elements 102, 104, & 108, column 5, lines 21-25, "Since the real time multimedia data is ultimately destined for a client that accesses the packet-switched network via a direct dialup network, the packet-switched network must interface with a gateway that is coupled to the circuit-switched network", The gateway connects a PSTN (circuit-switched network) to a packet-switched network.], said apparatus comprising:

decision means for deciding on whether data from at least one of said first and second communication networks has been delayed in arrival or lost [Cooklev, fig. 5, element 704, column 9, lines 39-43, "The packet processor 704 extracts the sequence number present in the header of every packet and detects, first, whether packets have arrived in order, and, second, the presence of packet los", The packet processor decides if there is delay (out of order) or packet loss.]; and

control means for performing control so that, if the result of said decision indicates that the data from at least one of said first and second communication networks has been delayed in arrival or lost, data for causing a destination terminal of

transmission on the other communication network to execute error concealment

processing is generated or data acquired is discarded [Cooklev, fig. 5, column 9,

element 710, column 9, lines 47-51, "Upon detection of a lost packet, the packet

processor 704 determines the importance of the lost packet. If the lost packet is

"important," the missing packet reconstruction block or process 710 tries to recover a

lower-quality version of the lost data from other packets", If the packet is lost and

deemed important, then the error concealment process begins to replicate a low quality

version of the lost packet.].

8.   **As per claim 56,** Cooklev teaches a method for processing encoded data by a

gateway apparatus for conducting connection between a first communication network

and a second communication network of respective different types [Cooklev, fig. 2,

elements 102, 104, & 108, column 5, lines 21-25, "Since the real time multimedia data is

ultimately destined for a client that accesses the packet-switched network via a direct

dialup network, the packet-switched network must interface with a gateway that is

coupled to the circuit-switched network", The gateway connects a PSTN (circuit-

switched network) to a packet-switched network.], said method comprising:

        (a) a step of said gateway apparatus deciding on whether data from at least one

of said first and second communication networks has been delayed in arriving or lost

[Cooklev, fig. 5, element 704, column 9, lines 39-43, "The packet processor 704 extracts

the sequence number present in the header of every packet and detects, first, whether

packets have arrived in order, and, second, the presence of packet los", The packet

processor decides if there is delay (out of order) or packet loss.]; and

(b) a step of said gateway apparatus generating data for causing a destination

terminal of transmission to execute error concealment processing or discarding

encoded data acquired, in case the result of said decision indicates that data from at

least one of said first and second communication networks has been delayed in arrival

or lost [Cooklev, fig. 5, column 9, element 710, column 9, lines 47-51, "Upon detection

of a lost packet, the packet processor 704 determines the importance of the lost packet.

If the lost packet is "important," the missing packet reconstruction block or process 710

tries to recover a lower-quality version of the lost data from other packets", If the packet

is lost and deemed important, then the error concealment process begins to replicate a

low quality version of the lost packet.].

9.   **As per claim 58,** Cooklev teaches the method for processing encoded data by a

gateway apparatus according to claim 56. Cooklev also teaches wherein said first

communication network is a packet-switched network [Cooklev, fig. 2, element 102,

column 6, line 62, "A packet network 102"] and said second communication network is a

line-switched network [Cooklev, fig. 2, element 108, column 6, lines 65-66, "a circuit-

switched network such as PSTN 108", The circuit switched network (or PSTN) is a line-

switched network.];

said method further comprising:

(a2) a step of said gateway apparatus deciding on whether encoded data from

said packet-switched network has been delayed in arrival or lost [Cooklev, fig. 5,

element 704, column 9, lines 39-43, "The packet processor 704 extracts the sequence

number present in the header of every packet and detects, first, whether packets have

arrived in order, and, second, the presence of packet los", The packet processor

decides if there is delay (out of order) or packet loss.]; and

(b2) a step of said gateway apparatus generating data for causing a destination

terminal of transmission to execute error concealment processing or discarding

encoded data acquired in case the result of said decision indicates that the encoded

data from said packet- switched network has been delayed in arrival or lost [Cooklev,

fig. 5, column 9, element 710, column 9, lines 47-51, "Upon detection of a lost packet,

the packet processor 704 determines the importance of the lost packet. If the lost

packet is "important," the missing packet reconstruction block or process 710 tries to

recover a lower-quality version of the lost data from other packets", If the packet is lost

and deemed important, then the error concealment process begins to replicate a low

quality version of the lost packet.].

10.   **As per claim 68,** Cooklev teaches a method for processing encoded data from

at least one communication network out of a line-switched network and a packet-

switched network to the other communication network in a gateway system conducting

connection between said line-switched network and said packet-switched network of

respective different types [Cooklev, fig. 2, elements 102, 104, & 108, column 5, lines 21-

25, "Since the real time multimedia data is ultimately destined for a client that accesses

the packet-switched network via a direct dialup network, the packet-switched network

must interface with a gateway that is coupled to the circuit-switched network", The

gateway connects a PSTN (circuit-switched network) to a packet-switched network.],

said method comprising:

in case encoded data from at least one of said line-switched network and the

packet-switched network has been delayed in arriving or lost [Cooklev, fig. 5, element

704, column 9, lines 39-43, "The packet processor 704 extracts the sequence number

present in the header of every packet and detects, first, whether packets have arrived in

order, and, second, the presence of packet los", The packet processor decides if there

is delay (out of order) or packet loss.], performing processing for generating data for

causing a destination terminal of transmission on the other communication network to

execute error concealment processing, or discarding the encoded data acquired to send

said encoded data [Cooklev, fig. 5, column 9, element 710, column 9, lines 47-51,

"Upon detection of a lost packet, the packet processor 704 determines the importance

of the lost packet. If the lost packet is "important," the missing packet reconstruction

block or process 710 tries to recover a lower-quality version of the lost data from other

packets", If the packet is lost and deemed important, then the error concealment

process begins to replicate a low quality version of the lost packet.].

11.   **As per claim 70,** Cooklev teaches a gateway apparatus for connecting a packet-

switched network and a line-switched network [Cooklev, fig. 2, elements 102, 104, &

108, column 5, lines 21-25, "Since the real time multimedia data is ultimately destined

for a client that accesses the packet-switched network via a direct dialup network, the

packet-switched network must interface with a gateway that is coupled to the circuit-

switched network", The gateway connects a PSTN (circuit-switched network) to a

packet-switched network.], comprising:

an encoding data extracting unit which, if packets are not received from said

packet-switched network at a preset period such that packet delay has been produced,

and encoded data are to be extracted from packet data received [Cooklev, fig. 5,

element 704, column 9, lines 41-44, "The packet processor 704 extracts the sequence

number present in the header of every packet and detects, first, whether packets have

arrived in order, and, second, the presence of packet loss. The packet processor 704

performs, if necessary, packet re-ordering", Since the packet number extracts the

number of packets in the buffer and is capable of reordering them, it uses the counted

of the data in the buffer to perform these operations.], outputs a signal to the effect that

packet data has failed to be acquired [Cooklev, fig. 5, "Lost Important Packet", This step

proceeds to the missing packet re-constructor.]; and

a controller which generates or discards encoded data based on an output from

said encoding data extracting unit to perform control for outputting encoded data to said

line-switched network [Cooklev, fig. 5, column 9, element 710, column 9, lines 47-51,

"Upon detection of a lost packet, the packet processor 704 determines the importance

of the lost packet. If the lost packet is "important," the missing packet reconstruction

block or process 710 tries to recover a lower-quality version of the lost data from other

packets", If the packet is lost and deemed important, then the error concealment

process begins to replicate a low quality version of the lost packet.].

Claim Rejections - 35 USC § 103

12.   **The following is a quotation of 35 U.S.C. 103(a) which forms the basis for**

all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

13.   Claims 49-55, 57, 59-62, & 71 are rejected under 35 U.S.C. 103(a) as being unpatentable over Cooklev (US Patent No. 6,574,218) in view of Joseph et al. (US Patent No. 6,973,024).

14.   **As per claim 49,** Cooklev teaches the gateway apparatus according to claim 48. Cooklev also teaches wherein

said first communication network is a line-switched network [Cooklev, fig. 2, element 108, column 6, lines 65-66, "a circuit-switched network such as PSTN 108", The circuit switched network (or PSTN) is a line-switched network.]; and

said second communication network is a packet-switched network [Cooklev, fig. 2, element 102, column 6, line 62, "A packet network 102"].

Cooklev et al. does not teach wherein said apparatus comprises: first decision means for deciding on whether encoded data from said line-switched network has been delayed in arrival or lost; and first control means for performing control so that, if the result of said decision indicates that said encoded data has been delayed in arrival or lost, encoded data for causing a destination terminal of transmission on said packet-switched network to execute error concealment processing is generated or the encoded data acquired is discarded.

However, Joseph et al. teaches wherein said apparatus comprises: first decision means for deciding on whether encoded data from said line-switched network has been delayed in arrival or lost [Joseph, fig. 3, elements 16, 22, & 24, column 5, lines 49-52, "A

revertive switchover is a switchover that takes place after standby modem element 22

has been switched into service due to a failure of main modem element 24", Once a

modem has failed, data coming from the PSTN will be lost. In response to this, a switch

is made from one modem to another.]; and

first control means for performing control so that, if the result of said decision

indicates that said encoded data has been delayed in arrival or lost, encoded data for

causing a destination terminal of transmission on said packet-switched network to

execute error concealment processing is generated or the encoded data acquired is

discarded [Joseph, fig. 3, elements 16, 22, & 24, column 5, lines 60-64, "The switchover

that occurs after an unanticipated failure uses the same basic methodology, but since

one modem element has failed and some time, however short, must pass before a

failure can be detected, some data may be lost during the switchover time", Since

modem failure caused the switchover, some data will be lost as a result.].

Thus it would have been obvious to one of ordinary skill in the art at the time the

invention was made to implement the teachings of Joseph et al. into Cooklev, since

Cooklev et al. suggests a media gateway between a PSTN and IP network that

performs error handling for packets, and Joseph et al. suggests the beneficial use of a

media gateway between a PSTN and IP network such as to perform error handling for

lost voice traffic [Joseph, fig. 3, elements 16, 22, & 24, column 5, lines 49-52 & 60-64] in

the analogous art of media gateways.

15.   **As per claim 50,** Cooklev teaches the gateway apparatus according to claim 48.

Cooklev also teaches wherein

said first communication network is a line-switched network [Cooklev, fig. 2,

element 108, column 6, lines 65-66, "a circuit-switched network such as PSTN 108",

The circuit switched network (or PSTN) is a line-switched network.]; and

said second communication network is a packet-switched network [Cooklev, fig.

2, element 102, column 6, line 62, "A packet network 102"]; and wherein

said decision means comprises:

second decision means for deciding on whether encoded data from said packet-

switched network have been delayed in arriving or lost [Cooklev, fig. 5, element 704,

column 9, lines 39-43, "The packet processor 704 extracts the sequence number

present in the header of every packet and detects, first, whether packets have arrived in

order, and, second, the presence of packet los", The packet processor decides if there

is delay (out of order) or packet loss.].

Cooklev et al. does not teach second control means for performing control so

that, if the result of said decision indicates that the encoded data from said line-switched

network has been delayed in arrival or lost, encoded data for causing a destination

terminal of transmission on the side of said line-switched network to execute error

concealment processing is generated, or the encoded data delayed in arrival is

discarded.

However, Joseph et al. teaches second control means for performing control so

that, if the result of said decision indicates that the encoded data from said line-switched

network has been delayed in arrival or lost, encoded data for causing a destination

terminal of transmission on the side of said line-switched network to execute error

concealment processing is generated, or the encoded data delayed in arrival is discarded [Joseph, fig. 3, elements 16, 22, & 24, column 5, lines 60-64, "The switchover that occurs after an unanticipated failure uses the same basic methodology, but since one modem element has failed and some time, however short, must pass before a failure can be detected, some data may be lost during the switchover time", Since modem failure caused the switchover, some data will be lost as a result.].

Thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to implement the teachings of Joseph et al. into Cooklev, since Cooklev et al. suggests a media gateway between a PSTN and IP network that performs error handling for packets, and Joseph et al. suggests the beneficial use of a media gateway between a PSTN and IP network such as to perform error handling for lost voice traffic [Joseph, fig. 3, elements 16, 22, & 24, column 5, lines 60-64] in the analogous art of media gateways.

16.   **As per claim 51,** Cooklev in view of Joseph et al. teaches the gateway apparatus according to claim 49. Cooklev also teaches wherein

said decision means comprises:

second decision means for deciding on whether encoded data from said packet-switched network have been delayed in arriving or lost [Cooklev, fig. 5, element 704, column 9, lines 39-43, "The packet processor 704 extracts the sequence number present in the header of every packet and detects, first, whether packets have arrived in order, and, second, the presence of packet los", The packet processor decides if there is delay (out of order) or packet loss.]; and

second control means for performing control so that, if the result of said decision

indicates that the encoded data from said line-switched network has been delayed in

arrival or lost, encoded data for causing a destination terminal of transmission on the

side of said line-switched network to execute error concealment processing is

generated, or the encoded data delayed in arrival is discarded [Cooklev, fig. 5, column

9, element 710, column 9, lines 47-51, "Upon detection of a lost packet, the packet

processor 704 determines the importance of the lost packet. If the lost packet is

"important," the missing packet reconstruction block or process 710 tries to recover a

lower-quality version of the lost data from other packets", If the packet is lost and

deemed important, then the error concealment process begins to replicate a low quality

version of the lost packet.].

17.   **As per claim 52,** Cooklev teaches a gateway apparatus for conducting

connection between a first communication network and a second communication

network of respective different types [Cooklev, fig. 2, elements 102, 104, & 108, column

5, lines 21-25, "Since the real time multimedia data is ultimately destined for a client that

accesses the packet-switched network via a direct dialup network, the packet-switched

network must interface with a gateway that is coupled to the circuit-switched network",

The gateway connects a PSTN (circuit-switched network) to a packet-switched

network.], said apparatus comprising:

decision means for deciding on whether encoded data from at least one of said

first and second communication networks has been delayed in arrival or lost [Cooklev,

fig. 5, element 704, column 9, lines 39-43, "The packet processor 704 extracts the

sequence number present in the header of every packet and detects, first, whether

packets have arrived in order, and, second, the presence of packet los", The packet

processor decides if there is delay (out of order) or packet loss.];

control means for performing control so that, if the result of said decision

indicates that the encoded data from at least one of said first and second

communication networks has been delayed in arrival or lost, data is generated by error

concealment processing, or data acquired is discarded [Cooklev, fig. 5, column 9,

element 710, column 9, lines 47-51, "Upon detection of a lost packet, the packet

processor 704 determines the importance of the lost packet. If the lost packet is

"important," the missing packet reconstruction block or process 710 tries to recover a

lower-quality version of the lost data from other packets", If the packet is lost and

deemed important, then the error concealment process begins to replicate a low quality

version of the lost packet.].

Cooklev does not teach decoding means for decoding encoded data from said at

least one communication network, processed by said control means, and for outputting

the resulting decoded data; and encoding means for encoding the data obtained from

said error concealment processing by said control means, and said decoded data, in

accordance with an encoding system different from the encoding system for said

encoded data from said one communication network.

However, Joseph et al. teaches decoding means for decoding encoded data from

said at least one communication network, processed by said control means, and for

outputting the resulting decoded data [Joseph, fig. 1, elements 12, 16, & 18, column 4,

lines 16-19, "Media gateway 12 may also decompress, decode, and reassemble

terminating voice traffic (i.e., egress traffic) for handoff to PSTN 16 via the local carrier's

network", The packet traffic is decoded into data, where it is then encoded into voice

traffic format for PSTN networks.]; and

encoding means for encoding the data obtained from said error concealment

processing by said control means, and said decoded data, in accordance with an

encoding system different from the encoding system for said encoded data from said

one communication network [Joseph, fig. 1, elements 12, 16, & 18, column 4, lines 16-

19, "Media gateway 12 may also decompress, decode, and reassemble terminating

voice traffic (i.e., egress traffic) for handoff to PSTN 16 via the local carrier's network",

The packet traffic is decoded into data, where it is then encoded into voice traffic format

for PSTN networks.].

Thus it would have been obvious to one of ordinary skill in the art at the time the

invention was made to implement the teachings of Joseph et al. into Cooklev, since

Cooklev suggests a media gateway between a PSTN and IP network, and Joseph et al.

suggests the beneficial use of a media gateway between a PSTN and IP network such

as to convert between each network's encoded data [Joseph, fig. 1, elements 12, 16, &

18, column 4, lines 16-19] in the analogous art of media gateways.

18.   **As per claim 53,** Cooklev in view of Joseph et al. teaches the gateway

apparatus according to claim 52. Cooklev also teaches wherein

said first communication network is a line-switched network [Cooklev, fig. 2,

element 108, column 6, lines 65-66, "a circuit-switched network such as PSTN 108",

The circuit switched network (or PSTN) is a line-switched network.]; and wherein

said second communication network is a packet-switched network [Cooklev, fig.

2, element 102, column 6, line 62, "A packet network 102"].

Cooklev does not teach said apparatus comprising: first decision means for

deciding on whether the encoded data from said line-switched network have been

delayed in arrival or lost; first control means for performing control so that, if the result of

decision indicates that the encoded data from said line-switched network has been

delayed in arrival or lost, data is generated by error concealment processing, or the

acquired encoded data is discarded; first decoding means for decoding the encoded

data from said line-switched network, as processed by said first control means, and for

outputting the resulting decoded data; and first encoding means for encoding the data

obtained from said error concealment processing from said first control means and said

decoded data from said first decoding means in accordance with an encoding system

different from the encoding system for said encoded data from said line-switched

network.

However, Joseph et al. teaches said apparatus comprising:

first decision means for deciding on whether the encoded data from said

line-switched network have been delayed in arrival or lost [Joseph, fig. 3, elements 16,

22, & 24, column 5, lines 49-52, "A revertive switchover is a switchover that takes place

after standby modem element 22 has been switched into service due to a failure of main

modem element 24", Once a modem has failed, data coming from the PSTN will be lost.

In response to this, a switch is made from one modem to another.];

first control means for performing control so that, if the result of decision

indicates that the encoded data from said line-switched network has been delayed in

arrival or lost, data is generated by error concealment processing, or the acquired

encoded data is discarded [Joseph, fig. 3, elements 16, 22, & 24, column 5, lines 60-64,

"The switchover that occurs after an unanticipated failure uses the same basic

methodology, but since one modem element has failed and some time, however short,

must pass before a failure can be detected, some data may be lost during the

switchover time", Since modem failure caused the switchover, some data will be lost as

a result.];

first decoding means for decoding the encoded data from said line-switched

network, as processed by said first control means, and for outputting the resulting

decoded data [Joseph, fig. 1, elements 12, 16, & 18, column 4, lines 12-16, "Media

gateway 12 serves as an interface between the PSTN and IP network, and it may

typically digitize, encode, and compress originating voice traffic (i.e., ingress traffic) into

packets for transport over managed IP networks", The gateway decodes (digitizes)

voice data from the PSTN and then encodes it into packets for the IP network.]; and

first encoding means for encoding the data obtained from said error concealment

processing from said first control means and said decoded data from said first decoding

means in accordance with an encoding system different from the encoding system for

said encoded data from said line-switched network [Joseph, fig. 1, elements 12, 16, &

18, column 4, lines 12-16, "Media gateway 12 serves as an interface between the PSTN

and IP network, and it may typically digitize, encode, and compress originating voice

traffic (i.e., ingress traffic) into packets for transport over managed IP networks", The

gateway decodes (digitizes) voice data from the PSTN and then encodes it into packets

for the IP network.].

    Thus it would have been obvious to one of ordinary skill in the art at the time the

invention was made to implement the teachings of Joseph et al. into Cooklev, since

Cooklev et al. suggests a media gateway between a PSTN and IP network that

performs error handling for packets, and Joseph et al. suggests the beneficial use of a

media gateway between a PSTN and IP network such as to perform error handling for

lost voice traffic and to convert between each network's encoded data [Joseph, fig. 1,

elements 12, 16, & 18, column 4, lines 16-19 & fig. 3, elements 16, 22, & 24, column 5,

lines 49-52 & 60-64] in the analogous art of media gateways.

19.   **As per claim 54,** Cooklev in view of Joseph et al. teaches the gateway

apparatus according to claim 52. Cooklev also teaches wherein

    said first communication network is a line-switched network [Cooklev, fig. 2,

element 108, column 6, lines 65-66, "a circuit-switched network such as PSTN 108",

The circuit switched network (or PSTN) is a line-switched network.]; and

    said second communication network is a packet-switched network [Cooklev, fig.

2, element 102, column 6, line 62, "A packet network 102"]; and wherein

    said apparatus comprises:

second decision means for deciding on whether the encoded data from said

packet-switched network have been delayed in arrival or lost [Cooklev, fig. 5, element

704, column 9, lines 39-43, "The packet processor 704 extracts the sequence number

present in the header of every packet and detects, first, whether packets have arrived in

order, and, second, the presence of packet los", The packet processor decides if there

is delay (out of order) or packet loss.].

Cooklev does not teach second control means for performing control so that, if

the result of decision indicates that the encoded data from said line-switched network

has been delayed in arrival or lost, data is generated by error concealment processing,

or the acquired encoded data is discarded; second decoding means for decoding the

encoded data from said packet-switched network, as processed by said second control

means, and for outputting the resulting decoded data; and second encoding means for

encoding the data obtained from said error concealment processing from said second

control means and said decoded data from said second decoding means in accordance

with an encoding system different from the encoding system for said encoded data from

said packet-switched network.

However, Joseph et al. teaches second control means for performing control so

that, if the result of decision indicates that the encoded data from said line-switched

network has been delayed in arrival or lost, data is generated by error concealment

processing, or the acquired encoded data is discarded [Joseph, fig. 3, elements 16, 22,

& 24, column 5, lines 60-64, "The switchover that occurs after an unanticipated failure

uses the same basic methodology, but since one modem element has failed and some

time, however short, must pass before a failure can be detected, some data may be lost

during the switchover time", Since modem failure caused the switchover, some data will

be lost as a result.];

second decoding means for decoding the encoded data from said packet-

switched network, as processed by said second control means, and for outputting the

resulting decoded data [Joseph, fig. 1, elements 12, 16, & 18, column 4, lines 16-19,

"Media gateway 12 may also decompress, decode, and reassemble terminating voice

traffic (i.e., egress traffic) for handoff to PSTN 16 via the local carrier's network", The

packet traffic is decoded into data, where it is then encoded into voice traffic format for

PSTN networks.]; and

second encoding means for encoding the data obtained from said error

concealment processing from said second control means and said decoded data from

said second decoding means in accordance with an encoding system different from the

encoding system for said encoded data from said packet-switched network [Joseph, fig.

1, elements 12, 16, & 18, column 4, lines 16-19, "Media gateway 12 may also

decompress, decode, and reassemble terminating voice traffic (i.e., egress traffic) for

handoff to PSTN 16 via the local carrier's network", The packet traffic is decoded into

data, where it is then encoded into voice traffic format for PSTN networks.].

Thus it would have been obvious to one of ordinary skill in the art at the time the

invention was made to implement the teachings of Joseph et al. into Cooklev, since

Cooklev et al. suggests a media gateway between a PSTN and IP network that

performs error handling for packets, and Joseph et al. suggests the beneficial use of a

media gateway between a PSTN and IP network such as to perform error handling for

lost voice traffic and to convert between each network's encoded data [Joseph, fig. 1,

elements 12, 16, & 18, column 4, lines 16-19 & fig. 3, elements 16, 22, & 24, column 5,

lines 60-64] in the analogous art of media gateways.

20.   **As per claim 55,** Cooklev in view of Joseph et al. teaches the gateway

apparatus according to claim 53. Cooklev also teaches wherein

        said apparatus comprises:

        second decision means for deciding on whether the encoded data from said

packet-switched network have been delayed in arrival or lost [Cooklev, fig. 5, element

704, column 9, lines 39-43, "The packet processor 704 extracts the sequence number

present in the header of every packet and detects, first, whether packets have arrived in

order, and, second, the presence of packet los", The packet processor decides if there

is delay (out of order) or packet loss.].

        Cooklev does not teach second control means for performing control so that, if

the result of decision indicates that the encoded data from said line-switched network

has been delayed in arrival or lost, data is generated by error concealment processing,

or the acquired encoded data is discarded; second decoding means for decoding the

encoded data from said packet-switched network, as processed by said second control

means, and for outputting the resulting decoded data; and second encoding means for

encoding the data obtained from said error concealment processing from said second

control means and said decoded data from said second decoding means in accordance

with an encoding system different from the encoding system for said encoded data from said packet-switched network.

However, Joseph et al. teaches second control means for performing control so that, if the result of decision indicates that the encoded data from said line-switched network has been delayed in arrival or lost, data is generated by error concealment processing, or the acquired encoded data is discarded [Joseph, fig. 3, elements 16, 22, & 24, column 5, lines 60-64, "The switchover that occurs after an unanticipated failure uses the same basic methodology, but since one modem element has failed and some time, however short, must pass before a failure can be detected, some data may be lost during the switchover time", Since modem failure caused the switchover, some data will be lost as a result.];

second decoding means for decoding the encoded data from said packet-switched network, as processed by said second control means, and for outputting the resulting decoded data [Joseph, fig. 1, elements 12, 16, & 18, column 4, lines 16-19, "Media gateway 12 may also decompress, decode, and reassemble terminating voice traffic (i.e., egress traffic) for handoff to PSTN 16 via the local carrier's network", The packet traffic is decoded into data, where it is then encoded into voice traffic format for PSTN networks.]; and

second encoding means for encoding the data obtained from said error concealment processing from said second control means and said decoded data from said second decoding means in accordance with an encoding system different from the encoding system for said encoded data from said packet-switched network [Joseph, fig.

1, elements 12, 16, & 18, column 4, lines 16-19, "Media gateway 12 may also

decompress, decode, and reassemble terminating voice traffic (i.e., egress traffic) for

handoff to PSTN 16 via the local carrier's network", The packet traffic is decoded into

data, where it is then encoded into voice traffic format for PSTN networks.].

Thus it would have been obvious to one of ordinary skill in the art at the time the

invention was made to implement the teachings of Joseph et al. into Cooklev, since

Cooklev et al. suggests a media gateway between a PSTN and IP network that

performs error handling for packets, and Joseph et al. suggests the beneficial use of a

media gateway between a PSTN and IP network such as to perform error handling for

lost voice traffic and to convert between each network's encoded data [Joseph, fig. 1,

elements 12, 16, & 18, column 4, lines 16-19 & fig. 3, elements 16, 22, & 24, column 5,

lines 60-64] in the analogous art of media gateways.

21.   **As per claim 57,** Cooklev teaches the method for processing encoded data by a

gateway apparatus according to claim 56. Cooklev also teaches wherein said first

communication network is a line-switched network [Cooklev, fig. 2, element 108, column

6, lines 65-66, "a circuit-switched network such as PSTN 108", The circuit switched

network (or PSTN) is a line-switched network.] and said second communication network

is a packet-switched network [Cooklev, fig. 2, element 102, column 6, line 62, "A packet

network 102"].

Cooklev et al. does not teach said method further comprising: (a1) a step of said

gateway apparatus deciding on whether encoded data from said line-switched network

has been delayed in arrival or lost; and (b1) a step of said gateway apparatus

generating encoded data for causing a destination terminal of transmission to execute

error concealment processing or discarding encoded data acquired in case the result of

said decision indicates that data from said line- switched network has been delayed in

arrival or lost.

However, Joseph et al. teaches said method further comprising:

(a1) a step of said gateway apparatus deciding on whether encoded data from

said line-switched network has been delayed in arrival or lost [Joseph, fig. 3, elements

16, 22, & 24, column 5, lines 49-52, "A revertive switchover is a switchover that takes

place after standby modem element 22 has been switched into service due to a failure

of main modem element 24", Once a modem has failed, data coming from the PSTN will

be lost. In response to this, a switch is made from one modem to another.]; and

(b1) a step of said gateway apparatus generating encoded data for causing a

destination terminal of transmission to execute error concealment processing or

discarding encoded data acquired in case the result of said decision indicates that data

from said line-switched network has been delayed in arrival or lost [Joseph, fig. 3,

elements 16, 22, & 24, column 5, lines 60-64, "The switchover that occurs after an

unanticipated failure uses the same basic methodology, but since one modem element

has failed and some time, however short, must pass before a failure can be detected,

some data may be lost during the switchover time", Since modem failure caused the

switchover, some data will be lost as a result.].

Thus it would have been obvious to one of ordinary skill in the art at the time the

invention was made to implement the teachings of Joseph et al. into Cooklev, since

Cooklev et al. suggests a media gateway between a PSTN and IP network that

performs error handling for packets, and Joseph et al. suggests the beneficial use of a

media gateway between a PSTN and IP network such as to perform error handling for

lost voice traffic [Joseph, fig. 3, elements 16, 22, & 24, column 5, lines 49-52 & 60-64] in

the analogous art of media gateways.

22.   **As per claim 59,** Cooklev in view of Joseph et al. teaches the method for

processing encoded data by a gateway apparatus according to claim 57. Cooklev also

teaches wherein said first communication network is a packet-switched network

[Cooklev, fig. 2, element 102, column 6, line 62, "A packet network 102"] and said

second communication network is a line-switched network [Cooklev, fig. 2, element 108,

column 6, lines 65-66, "a circuit-switched network such as PSTN 108", The circuit

switched network (or PSTN) is a line-switched network.]; said method further

comprising:

        (a2) a step of said gateway apparatus deciding on whether encoded data from

said packet-switched network has been delayed in arrival or lost [Cooklev, fig. 5,

element 704, column 9, lines 39-43, "The packet processor 704 extracts the sequence

number present in the header of every packet and detects, first, whether packets have

arrived in order, and, second, the presence of packet los", The packet processor

decides if there is delay (out of order) or packet loss.]; and

        (b2) a step of said gateway apparatus generating data for causing a destination

terminal of transmission to execute error concealment processing or discarding

encoded data acquired in case the result of said decision indicates that the encoded

data from said packet-switched network has been delayed in arrival or lost [Cooklev, fig. 5, column 9, element 710, column 9, lines 47-51, "Upon detection of a lost packet, the packet processor 704 determines the importance of the lost packet. If the lost packet is "important," the missing packet reconstruction block or process 710 tries to recover a lower-quality version of the lost data from other packets", If the packet is lost and deemed important, then the error concealment process begins to replicate a low quality version of the lost packet.].

23.   **As per claim 60,** Cooklev teaches a method for processing encoded data by a gateway apparatus for conducting connection between a first communication network and a second communication network of respective different types [Cooklev, fig. 2, elements 102, 104, & 108, column 5, lines 21-25, "Since the real time multimedia data is ultimately destined for a client that accesses the packet-switched network via a direct dialup network, the packet-switched network must interface with a gateway that is coupled to the circuit-switched network", The gateway connects a PSTN (circuit-switched network) to a packet-switched network.], comprising:

(a) a step of said gateway apparatus deciding on whether data from at least one of said first and second communication networks has been delayed in arriving or lost [Cooklev, fig. 5, element 704, column 9, lines 39-43, "The packet processor 704 extracts the sequence number present in the header of every packet and detects, first, whether packets have arrived in order, and, second, the presence of packet los", The packet processor decides if there is delay (out of order) or packet loss.]; and

(b) a step of said gateway apparatus generating data by error concealment

processing or discarding encoded data acquired in case the result of said decision

indicates that data from at least one of said first and second communication networks

has been delayed in arrival or lost [Cooklev, fig. 5, column 9, element 710, column 9,

lines 47-51, "Upon detection of a lost packet, the packet processor 704 determines the

importance of the lost packet. If the lost packet is "important," the missing packet

reconstruction block or process 710 tries to recover a lower-quality version of the lost

data from other packets", If the packet is lost and deemed important, then the error

concealment process begins to replicate a low quality version of the lost packet.].

Cooklev does not teach (c) a step of said gateway apparatus decoding encoded

data from said at least one communication network, processed in said step (b), and

outputting decoded data; and (d) a step of said gateway apparatus encoding the data

obtained by said error concealment processing and said decoded data in accordance

with an encoding system different from that for encoded data from said one

communication network and outputting the resulting data.

However, Joseph et al. teaches (c) a step of said gateway apparatus decoding

encoded data from said at least one communication network, processed in said step (b),

and outputting decoded data [Joseph, fig. 1, elements 12, 16, & 18, column 4, lines 16-

19, "Media gateway 12 may also decompress, decode, and reassemble terminating

voice traffic (i.e., egress traffic) for handoff to PSTN 16 via the local carrier's network",

The packet traffic is decoded into data, where it is then encoded into voice traffic format

for PSTN networks.]; and

(d) a step of said gateway apparatus encoding the data obtained by said error

concealment processing and said decoded data in accordance with an encoding system

different from that for encoded data from said one communication network and

outputting the resulting data [Joseph, fig. 1, elements 12, 16, & 18, column 4, lines 16-

19, "Media gateway 12 may also decompress, decode, and reassemble terminating

voice traffic (i.e., egress traffic) for handoff to PSTN 16 via the local carrier's network",

The packet traffic is decoded into data, where it is then encoded into voice traffic format

for PSTN networks.].

Thus it would have been obvious to one of ordinary skill in the art at the time the

invention was made to implement the teachings of Joseph et al. into Cooklev, since

Cooklev suggests a media gateway between a PSTN and IP network, and Joseph et al.

suggests the beneficial use of a media gateway between a PSTN and IP network such

as to convert between each network's encoded data [Joseph, fig. 1, elements 12, 16, &

18, column 4, lines 16-19] in the analogous art of media gateways.

24.   **As per claim 61,** Cooklev et al. in view of Joseph et al. teaches the method for

processing encoded data by a gateway apparatus according to claim 60. Cooklev et al.

also teaches wherein

said first communication network is a line-switched network [Cooklev, fig. 2,

element 108, column 6, lines 65-66, "a circuit-switched network such as PSTN 108",

The circuit switched network (or PSTN) is a line-switched network.]; and

said second communication network is a packet-switched network [Cooklev, fig.

2, element 102, column 6, line 62, "A packet network 102"];

Cooklev does not teach said method further comprising: (a1) a step of said

gateway apparatus deciding on whether encoded data from said line-switched network

has been delayed in arrival or lost; (b1) a step of said gateway apparatus generating

data by error concealment processing or discarding encoded data acquired in case the

result of said decision indicates that the encoded data from said line-switched network

has been delayed in arriving or lost; (c1) a step of said gateway apparatus decoding

encoded data from said line-switched network, processed in said step (b1) and

outputting the resulting decoded data; and (d1) a step of said gateway apparatus

encoding the data obtained by said error concealment processing and said decoded

data in accordance with an encoding system different from that for encoded data from

said line-switched network and outputting the resulting data

However, Joseph et al. teaches said method further comprising:

(a1) a step of said gateway apparatus deciding on whether encoded data from

said line-switched network has been delayed in arrival or lost [Joseph, fig. 3, elements

16, 22, & 24, column 5, lines 49-52, "A revertive switchover is a switchover that takes

place after standby modem element 22 has been switched into service due to a failure

of main modem element 24", Once a modem has failed, data coming from the PSTN will

be lost. In response to this, a switch is made from one modem to another.]; and

(b1) a step of said gateway apparatus generating data by error concealment

processing or discarding encoded data acquired in case the result of said decision

indicates that the encoded data from said line-switched network has been delayed in

arriving or lost [Joseph, fig. 3, elements 16, 22, & 24, column 5, lines 60-64, "The

switchover that occurs after an unanticipated failure uses the same basic methodology, but since one modem element has failed and some time, however short, must pass before a failure can be detected, some data may be lost during the switchover time", Since modem failure caused the switchover, some data will be lost as a result.];

(c1) a step of said gateway apparatus decoding encoded data from said line-switched network, processed in said step (b1) and outputting the resulting decoded data [Joseph, fig. 1, elements 12, 16, & 18, column 4, lines 12-16, "Media gateway 12 serves as an interface between the PSTN and IP network, and it may typically digitize, encode, and compress originating voice traffic (i.e., ingress traffic) into packets for transport over managed IP networks", The gateway decodes (digitizes) voice data from the PSTN and then encodes it into packets for the IP network.]; and

(d1) a step of said gateway apparatus encoding the data obtained by said error concealment processing and said decoded data in accordance with an encoding system different from that for encoded data from said line-switched network and outputting the resulting data [Joseph, fig. 1, elements 12, 16, & 18, column 4, lines 12-16, "Media gateway 12 serves as an interface between the PSTN and IP network, and it may typically digitize, encode, and compress originating voice traffic (i.e., ingress traffic) into packets for transport over managed IP networks", The gateway decodes (digitizes) voice data from the PSTN and then encodes it into packets for the IP network.].

Thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to implement the teachings of Joseph et al. into Cooklev, since Cooklev et al. suggests a media gateway between a PSTN and IP network that

performs error handling for packets, and Joseph et al. suggests the beneficial use of a

media gateway between a PSTN and IP network such as to perform error handling for

lost voice traffic and to convert between each network's encoded data [Joseph, fig. 1,

elements 12, 16, & 18, column 4, lines 16-19 & fig. 3, elements 16, 22, & 24, column 5,

lines 49-52 & 60-64] in the analogous art of media gateways.

25.   **As per claim 62,** Cooklev in view of Joseph et al. teaches the method for

processing encoded data by a gateway apparatus according to claim 60. Cooklev also

teaches wherein said first communication network is a line-switched network [Cooklev,

fig. 2, element 108, column 6, lines 65-66, "a circuit-switched network such as PSTN

108", The circuit switched network (or PSTN) is a line-switched network.] and said

second communication network is a packet-switched network [Cooklev, fig. 2, element

102, column 6, line 62, "A packet network 102"]; said method further comprising:

        (a2) a step of said gateway apparatus deciding on whether encoded data from

said packet-switched network has been delayed in arrival or lost [Cooklev, fig. 5,

element 704, column 9, lines 39-43, "The packet processor 704 extracts the sequence

number present in the header of every packet and detects, first, whether packets have

arrived in order, and, second, the presence of packet los", The packet processor

decides if there is delay (out of order) or packet loss.]; and

        (b2) a step of said gateway apparatus generating data by error concealment

processing or discarding encoded data delayed in arriving in case the result of said

decision indicates that the encoded data from said line-switched network has been

delayed in arrival or lost [Cooklev, fig. 5, column 9, element 710, column 9, lines 47-51,

"Upon detection of a lost packet, the packet processor 704 determines the importance

of the lost packet. If the lost packet is "important," the missing packet reconstruction

block or process 710 tries to recover a lower-quality version of the lost data from other

packets", If the packet is lost and deemed important, then the error concealment

process begins to replicate a low quality version of the lost packet.].

Cooklev does not teach (c2) a step of said gateway apparatus decoding encoded

data from said packet- switched network, processed in said step (b2), and outputting the

resulting decoded data; and (d2) a step of said gateway apparatus encoding the data

obtained by said error concealment processing and said decoded data in accordance

with an encoding system different from that for encoded data from said packet-switched

network, and outputting the resulting data.

However, Joseph et al. teaches (c2) a step of said gateway apparatus decoding

encoded data from said packet- switched network, processed in said step (b2), and

outputting the resulting decoded data [Joseph, fig. 1, elements 12, 16, & 18, column 4,

lines 16-19, "Media gateway 12 may also decompress, decode, and reassemble

terminating voice traffic (i.e., egress traffic) for handoff to PSTN 16 via the local carrier's

network", The packet traffic is decoded into data, where it is then encoded into voice

traffic format for PSTN networks.]; and

(d2) a step of said gateway apparatus encoding the data obtained by said error

concealment processing and said decoded data in accordance with an encoding system

different from that for encoded data from said packet-switched network, and outputting

the resulting data [Joseph, fig. 1, elements 12, 16, & 18, column 4, lines 16-19, "Media

gateway 12 may also decompress, decode, and reassemble terminating voice traffic

(i.e., egress traffic) for handoff to PSTN 16 via the local carrier's network", The packet

traffic is decoded into data, where it is then encoded into voice traffic format for PSTN

networks.].

Thus it would have been obvious to one of ordinary skill in the art at the time the

invention was made to implement the teachings of Joseph et al. into Cooklev, since

Cooklev suggests a media gateway between a PSTN and IP network, and Joseph et al.

suggests the beneficial use of a media gateway between a PSTN and IP network such

as to convert between each network's encoded data [Joseph, fig. 1, elements 12, 16, &

18, column 4, lines 16-19] in the analogous art of media gateways.

26.   **As per claim 71,** The method for processing encoded data by a gateway

apparatus according to claim 61, said method further comprising:

(a2) a step of said gateway apparatus deciding on whether encoded data from

said packet-switched network has been delayed in arrival or lost [Cooklev, fig. 5,

element 704, column 9, lines 39-43, "The packet processor 704 extracts the sequence

number present in the header of every packet and detects, first, whether packets have

arrived in order, and, second, the presence of packet los", The packet processor

decides if there is delay (out of order) or packet loss.; and

(b2) a step of said gateway apparatus generating data by error concealment

processing or discarding encoded data delayed in arriving in case the result of said

decision indicates that the encoded data from said line-switched network has been

delayed in arrival or lost [Cooklev, fig. 5, column 9, element 710, column 9, lines 47-51,

"Upon detection of a lost packet, the packet processor 704 determines the importance

of the lost packet. If the lost packet is "important," the missing packet reconstruction

block or process 710 tries to recover a lower-quality version of the lost data from other

packets", If the packet is lost and deemed important, then the error concealment

process begins to replicate a low quality version of the lost packet.];

Cooklev et al. does not teach (c2) a step of said gateway apparatus decoding

encoded data from said packet- switched network, processed in said step (b2), and

outputting the resulting decoded data; and (d2) a step of said gateway apparatus

encoding the data obtained by said error concealment processing and said decoded

data in accordance with an encoded system different from that for encoded data from

said packet-switched network, and outputting the resulting data.

However, Joseph et al. teaches (c2) a step of said gateway apparatus decoding

encoded data from said packet- switched network, processed in said step (b2), and

outputting the resulting decoded data [Joseph, fig. 1, elements 12, 16, & 18, column 4,

lines 16-19, "Media gateway 12 may also decompress, decode, and reassemble

terminating voice traffic (i.e., egress traffic) for handoff to PSTN 16 via the local carrier's

network", The packet traffic is decoded into data, where it is then encoded into voice

traffic format for PSTN networks.]; and

(d2) a step of said gateway apparatus encoding the data obtained by said error

concealment processing and said decoded data in accordance with an encoded system

different from that for encoded data from said packet-switched network, and outputting

the resulting data [Joseph, fig. 1, elements 12, 16, & 18, column 4, lines 16-19, "Media

gateway 12 may also decompress, decode, and reassemble terminating voice traffic (i.e., egress traffic) for handoff to PSTN 16 via the local carrier's network", The packet traffic is decoded into data, where it is then encoded into voice traffic format for PSTN networks.].

Thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to implement the teachings of Joseph et al. into Cooklev, since Cooklev suggests a media gateway between a PSTN and IP network, and Joseph et al. suggests the beneficial use of a media gateway between a PSTN and IP network such as to convert between each network's encoded data [Joseph, fig. 1, elements 12, 16, & 18, column 4, lines 16-19] in the analogous art of media gateways.

Allowable Subject Matter

27.   Claims 64-67 & 69 are allowed.

Conclusion

28.   THIS ACTION IS MADE FINAL. Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of

the advisory action. In no event, however, will the statutory period for reply expire later

than SIX MONTHS from the mailing date of this final action.

29. **The Examiner has cited particular columns and line numbers or paragraphs

in the references applied to the claims above for the convenience of the

applicant.** Although the specified citations are representative of the teachings of the art

and are applied to specific limitations within the individual claim, other passages and

figures may apply as well. It is respectfully requested from the applicant in preparing

responses, to fully consider the references in their entirety as potentially teaching all or

part of the claimed invention, as well as the context of the passage as taught by the

prior art or disclosed by the Examiner.

In the case of amending the claimed invention, the Applicant is respectfully

requested to indicate the portion(s) of the specification which dictate(s) the structure

relied on for proper interpretation and also to verify and ascertain the metes and bounds

of the claimed invention.

30. **If the Applicant is of the opinion that an interview would help advance

prosecution in this case, they are welcome to call the Examiner, Paul Masur, at

the number listed below to schedule an interview.** The Examiner prefers interview

requests be accompanied with a detailed agenda via fax. The Examiner's fax number is

(571) 270-8297. The Examiner is willing to consider proposed amendments, clarify

rejections, and discuss any other issues that are presented by the Applicant. Please

note that the Examiner may not be able to accommodate all requests due to scheduling

constraints. It is recommended that interview requests be sent with ample time to schedule an interview.

31.   **Any inquiry concerning this communication or earlier communications from the examiner should be directed to Paul Masur whose telephone number is (571) 270-7297.** The examiner can normally be reached on Monday through Friday from 7:00AM to 4:30PM (Eastern Time).

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Ricky Ngo can be reached on (571) 272-3139. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Ricky Ngo/   /P. M./
Supervisory Patent Examiner, Art Unit 2416   Examiner, Art Unit 2416